(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau

Organization
International Bureau
OMI





(43) International Publication Date 11 March 2004 (11.03.2004)

PCT

(10) International Publication Number WO 2004/021025 A1

(51) International Patent Classification⁷: G01R 33/3415, G01N 24/08

(21) International Application Number:

PCT/AU2003/001116

(22) International Filing Date: 29 August 2003 (29.08.2003)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 2002951096

30 August 2002 (30.08.2002) AU

(71) Applicant (for all designated States except US): THE UNIVERSITY OF QUEENSLAND [AU/AU]; St Lucia, Queensland 4067 (AU).

(72) Inventors; and


(75) Inventors/Applicants (for US only): DODDRELL,
David, Michael [AU/AU]; 6 Lucerne Street, Westlake, Queensland 4074 (AU). CROZIER, Stuart
[AU/AU]; 60 Main Street, Wilston, Queensland 4051

(AU). LUESCHER, Kurt [AU/AU]; 108 Russell Terrace, Indooroopilly, Queensland 4068 (AU). ROFFMANN, Wolfgang, Udo [AU/AU]; 57 Tallowood Place, Mt Gravatt East, Queensland 4122 (AU).

- (74) Agent: CULLEN & CO; Level 26, 239 George Street, Brisbane, Queensland 4000 (AU).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: COIL ARRAY FOR MAGNETIC RESONANCE IMAGING



(57) Abstract: A radio frequency (RF) coil array is used in resonance imaging and/or analysis of a subject located within a cylindrical space in which a magnetic field is operatively applied in an axial direction (z). The coil array comprises a plurality of coil elements (10,11,12,13) angled relative to each other about the axis of the cylindrical space, each coil element having a pair of main conductors extending generally parallel to the direction of the magnetic field and located on diametrically opposite sides of the cylindrical space, and a pair of connection conductors connected between respective ends of the main conductors. Each coil element has its maximum sensitivity near the centre of the cylindrical space, so that the subject under study is located in a region of maximum sensitivity.

